M U.S. DEPT. COMM./NORA/DAD - DATA SECTION WORK FORM NO.1 DADWE1 FILD FLT 10: 9607 BKF FM: **TO:** BKF 4 FLT NO: 96 -034 BLK IN: 0600 ATA: 0016 ETD: BLK OUT: 20 56 ATD: 2103 ETE: BLK TIME: 3.4 FLT TIME: SPONSOR ORG: NOA-PROGRAM: STERAO PURPOSE: Aiv. C ARGUIST ORO PERSONNEL AC FENNEDY SYS ENG ROLES Ju TAGGART CP MCMILLAN, DATA SYS FOZAK NAV RADAR FE TORREY R DT/ODW RADIOSAINS SOUC CLD PHYS WHITE FD DOPPLER PARTICIPATING SCIENTIST/VISITORS/0A0 LAST, FIRST NAME ACTIVITY ON A/C AFFILIATION HUBLER, 6 SHERTDANP CMD( JOBSON, T WILCIAMS, I/RERSONTI KWITER / W WERT, B NCAR RARRISH, D AC BAPTELS, D/MATEJEA: PROPOSED/ACTUAL MISSION/REMARKS (RECCO, FIXES, STORM, PENET, NHOP #) 060/6.GIL 1020. Fub updat NAU will te INE#2

:

											0				
TIMP	LA	10	TA	TD	WD	ws	D	0 11	10	. A	i S				
Time 2103 2113					090	2	VCO	10	n u	0-1	<u> </u>	+	1		
2113			14.5	0.4	090 290	7 20	le	vel	12	k n	NC				
								· · ·			+				<u>.</u>
													1		
					1		1	1				-			• • • • • • • • • • • • • • • • • • • •
							ļ							1	
							<u> </u>							<u> </u>	
										-				1	
													-	1	
												1		1	
-													<u> </u>		
· · · · · · · · · · · · · · · · · · ·									ļ		ļ		<u>.</u>		
												; ; ;	 1		
												<u> </u>	1	1	
											1	; ;			
							ĺ					<u>.</u>	1		
													+		
													<u>.</u>	<u> </u>	
						•									
										<u> </u>			÷		a a a a a a a a a a a a a a a a a a a
													<u> </u>		
															<u> </u>
													-		
						_									
									4				1		1
															+
											10224				
and the second se										- CINE C	and the second second second	1			The second second second

STERAO 96

### FLIGHT #8 H960706

TYPE OF DATA	SENSOR OR OPTION				
INE	1				
Accelerometer	1				
Temperature probe	1				
Altitude change option	PA				
(for vertical winds)					
Static pressure	Rosemount fuselage				
Dynamic pressure	Rosemount fuselage				
Time source	Micro 99				
Constants file	CO2963.CON				

#### Notes:

There were eight time/data gaps: 2205:11 2205:20 2205:23 2205:30 0013:22 0013:30 0013:34 0013:40

The aircraft INE positions were renavigated with respect to GPS.

SPECIAL NOTE!!! Locations 80, 81 and 82 of record five on the standard tape contain vertical ground, vertical air and vertical speeds, respectively, computed using Dave Jorgensen's vertical wind algorithm. It is recommended that these values be used for vertical wind analysis.

Flight Meteorologist: Sean White: (813) 828-3310 ext. 3072

TITLE (MAX 21 CHARACTERS) -- EX HURRICANE PAINE STERAO FLIGHT 8 YYMMDDL FLT I.D. 960706H HHMMSS START TIME -99999 DEFAULT TO START OF DATA FOR PRINTOUT ONLY 210001 HHMMSS END TIME 999999 DEFAULT TO END OF DATA FOR PRINTOUT ONLY 001800 HHMMSS TAKE OFF TIME 210300 \* NUMBER OF TAPES (12) ...FOR STANDARD TAPE OUTPUT ONLY 6 \* -----LOGICAL UNIT OF INPUT DATA (I1) 5, 8 OR 9 FOR TAPE DRIVE 9 \* -----LOGICAL UNIT OF OUTPUT TAPE DRIVE (11) [FOR STANDARD TAPE ONLY] 9 \* -----LOGICAL UNIT OF PRINTER (11) 6 \* -----DATE OF PROGRAM (MMDDY) 06094 \* -----STATIC PRESSURE PROBE (I1) \* 1 = PSW (WINGTIP)\* 2 = PSF (CO-PILOT/FUSELAGE) \* 3 = FUTURE USE 2 \* -----DYNAMIC PRESSURE PROBE (11) \* 0 = PQW(WINGTIP)\* 1 = PQF1 (FUSELAGE 1281) \* 2 = PQF2 (FUSELAGE 1221) \* 3 =FUTURE US 1 \* -----INE SELECTION (I1) \* 1 = INE 1\* 2 = INE 21 \* -----ACCELEROMETER (I1) - USUALLY THE SAME AS YOUR INE SELECTION 1 \* ----- TOTAL TEMPERATURE PROBE (I1) [1 OR 2] 1 \* ----- DEWPONT TEMPERATURE PROBE (I1) [1 OR 2] 1 \* -----ALTIMETER OPTION (I1) - FOR VERTICAL WIND COMPUTATION \* 0 = PRESSURE ALTITUDE (OVER LAND) \* 1 = RADAR ALTITUDE APN-159 (OVER WATER) \* 2 = RADAR ALTITUDE APN-232 (OVER WATER) 0 \* -----PRINTOUT RATE SECONDS (I2) 30 \* -----WINDSPEED/DIRECTION RUNNING AVERAGE TIME, SECONDS (12) 10 ! FOR STANDARD TAPE OUTPUT ONLY \* -----TIME OPTION (I1) \* 1 = MICRO 29\* 2 = TIME BASED GENERATOR #1 \* 3 = TIME BASED GENEATOR #2 1 \* -----NAME OF CONSTANTS FILE EX CO3863.CON CO2963.CON 

96	0706F	1					
BAD BLC	ock						
)1;=2055 061-20	)						
:30	3						
20013:22							
:3	4						
. 1	U						
220000	+0.6 +0.	6					
23 0000	+0,8 -0,	ſ					
00 <del>0000</del> - 1800	-+1,4 -0	· (					
1000							

START: 2100:01

END: 001800

Flightplan Thunderstorm Study (with western variation) Colorado boundary-layer to free troposphere exchange

Doors closed: 13:50 Takeoff: 14:00 2103 Point A, Buckley National Guard Field 39 42 N. 104 45W

Calibration at constant altitude, Observer calls 12k Head direction of Pt. B (41 00N, 104 25W) at 15 kft MSL

Pt. A to Pt. B 150 km, ~ 19 min, (Climb < 10 min)

Stay at constant altitude for calibration, observer calls 14:00-14:25

(2113-2133)

avound B Far Cell

**Before the Storm** After Calibration descend to 1500 ft AGL along the way to Pt. C

Horizontal Survey within the PBL 2210 Pt. B to Pt. C (40 10N, 105 00W), to Pt. D (40 10N, 103 30W), to Pt. E (40 30N, 104 10W) 14:25-15:10

1800' 21397

Racetrack Profile up to 21 kft near Pt. E 2222 held Divec ==> Take first set of HC can samples at 1500 ft AGL, 13 kft, 17 kft, 21 kft MSL head east for 1 min 50 sec and climb at 1500 ft/min, reverse direction, head west for 1 min 50 sec. and on of Pt. F (40 10N, 104 25W) 410710 F (40 10N, 104 25W) 410710 F (40 10N, 104 25W) 410710 F (40 10N, 104 25W) F (5) F (40 10N, 104 25W) F (40 10N, 104 25W) F (5) F (continue climb etc up to 21 kft MSL) 15:10-15:20

Head direction of Pt. F (40 10N, 104 25W) Pt. E to Pt. F 60 km, 9 min 15:20-15:30

## Super Cell

IF during any part of the flight Operation Center identifies an isolated storm, fly boxes around the storm at max altitude, 21 kft MSL, 17 kft MSL, 13 kft MSL, and 1500 ft AGL.

The sides of the boxes have to be long enough for the radar characterization of the wind field and the distance from the storm is determined by the requirements of the doppler radar. The exact location of the boxes at a given altitude will depend on the movement of the storm cell.

Should the time that is required to fly this pattern be too long for the anticipated flight duration, limit the number of constant altitude boxes.

This pattern should satisfy both the radar and chemistry objectives of STERAO.

Concentrate on Western edge of squall line.

L-pattern on the southern (south-eastern) and the western side of the squall line.

I) Radar leg :	parallel to the line of storm cells at 2000 ft AGL from Lsw to Lse.					
II) Radar leg :	return from Bse to Bsw at 500 ft AGL.					
	Max length of these legs 15 min (~90 km).					
III) Radar leg :	perpendicular to the line of storms at the western edge of the					
	squall line, Bsw to Bnw at 500 ft AGL. Length of this leg is					
	determined by radar requirement.					
IV) Chemistry :	Return to Bse; either directly under the storm in a direct line from					
	Bnw to Bse or parallel to the radar legs, but in closer proximity to					
	the active storm cells at 500 ft AGL.					

Repeat this pattern II)-IV), if radar observations call for it. Adjust altitude if radio communication with CHILL require it.

V) Racetrack profile ahead of the squall line up to max altitude.

VI) If there is an anvil within the altitude range of the P3, descend to that altitude and attempt to approach the anvil by flying short legs (< 5 min) parallel to the line in progressively closer proximity to the storm (pilots disgression).

VII) Fly to the back side of the squall line around the storm at max altitude. Attempt again to approach the anvil region.

VIII) Racetrack profile behind the squall line.

IX) Radar and chemistry leg behind the squall line from Bne to Bnw.

21/5 2310 231 19/ (2319-2327) 17/ (2330-230) 15k (2339-2347)

If the radar indicates an anvil that is within the altitude range of the P3, attempt to transect part of the anvil if it is feasible and safe. Start these transect away from the cloud and attempt to move closer on subsequent transects.

## Hydrocarbon Profile between Pt. F and Pt. G

At 15:35 head direction of Pt. G (41 00N, 104 25W)

Hydrocarbon profile between Pt. F and Pt. G at 21 kft, 17 kft, 13 kft MSL, and 1500 ft AGL

Start HC-leg at : 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**)

500

# HC profile after the storm

North-South leg across the center of the last radar echo, the length of the HC-leg is approximately 100 km (not quite 1 deg latitude)

Hydrocarbon profile at 25 kft (or max altitude), 21 kft, 17 kft, 13 kft MSL, and 1500 ft AGL

Start HC-leg at :05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**)

19:20-20:35

(2347

Climb to 12 kft MSL for calibration

(Start NOy calibration, and stay at altitude for calibration 20:35-20:50, Observer calls)

Head direction of Buckley (39 42N, 104 45W) Pt. A ~ 20 min

Return to Buckley at ~21:00

Pt. A (39 42N, 104 45W)
Pt. B (41 00N, 104 25W)
Pt. C (40 10N, 105 00W)
Pt. D (40 10N, 103 30W)
Pt. E (40 30N, 104 10W)
Pt. F (40 10N, 104 25W)
Pt. G (41 00N, 104 25W)
other points will be determined during the flight.....

### 15:35-16:35

If at any point during this leg the **Observation Center** at the CHILL Radar site should indentify a target storm, switch to the **Active Storm Phase.** 

### **During the Active Storm Phase**

## Characterize Airflow with Radar and Characterize In-Flow Region of Cloud

Cloud identification and flight coordinates will be given by CHILL Radar,

### **Radar Legs:**

Straight lines parallel to and S to SW of the storm approximately 12 km away from the perimeter of the storm, orientation parallel to storm track at 7kft MSL (within the PBL, this should also be the inflow region of the storm)

until dissipation of storm.

Alternatives:	I) Straight leg parallel to the storm track.
===>	II) Fly L-pattern (south and west side of the storm).
===>	II) Repeat radar flight pattern at different altitude.
	(7kft, 16 kft, and > 22 kft MSL).
16:35-18:35	

## After Dissipation of the Storm:

Characterization of PBL after Storm Dissipation: Cross below location of the latest radar echo for 15 min (~100 km) 18:35-18:50

Characterization of Vertical Profile after Storm Dissipation

Race track Profile at location of the latest radar echo of the storm, descend to 500 ft AGL and then climb to max altitude at 1500 ft/min

==> Take second set of HC can samples at 1500 ft AGL, 13 kft, 17 kft, 21 kft MSL

18:50-19:20

Alternatives:

I) 16:35-17:50: If there is no appropriate storm identified in the study area, start HC profile between Pt. F (40 10N, 104 25W), and Pt. AH (40 10N, 103 25 W) at 1500 ft AGL, 13 kft MSL, 17 kft MSL, 21 kft MSL, 25 kft MSL.

II) 17:50-19:05: start HC profile between Pt. AH (40 10N, 103 25W) and AI (41 00N, 103 25W) at 25 kft MSL, 21 kft MSL, 17 kft MSL, 13 kft MSL, 1500 ft AGL

Climb to 12 kft MSL for calibration, 30 min

Return to Buckley

The detailed characterization of the 1 deg lat by 1 deg long box will hopefully help to pick the most appropriate orientation for the HC profiles for subsequent flights. It also allows to fall back into the thunderstorm mode at any time if appropriate storms should develop later on.



Alternative Orographic profile and Profile near Kremmling:

I) HC-Profile to the West of Ft. Collins.

Cross to Pt. BH (40 10N, 105 10 W) and adjust time for HC-Profile by flying N at 500 ft AGL and return to BH at start of HC profile If there is no appropriate storm identified in the study area, start HC profile between Pt. BH (40 10N, 105 10W), and Pt. BI (41 00N, 105 10 W) at 8 kft MSL, 13 kft MSL, 17 kft MSL, 21 kft MSL, 25 kft MSL. Start HC-leg at : 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**) 16:35-18:05:

II) HC-Profile near Kremmling
Head direction of Pt. BJ (41 00N, 106 30W) at 25 kft MSL
(Pt. BI to Pt. BJ 110 km, ~ 15 min) 18:05-18:20
HC Profile between Pt. BJ (41 00N, 106 30 W) and Pt. BK (40 00 N, 106 30 W)
at 21 kft MSL, 17 kft MSL, 15 kft MSL, 11 kft MSL (> 500 ft AGL)
Start HC-leg at : 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (Observer calls)
18:20-19:20

Climb to 15 kft MSL and return to Buckley, Calibration along the way. (Pt. BJ to Buckley 210 km, ~ 30 min) 19:50



EMERGENCY MESSAGE         TRANSMIT THE FOLLOWING MESSAGE TO ANY AGENCY ON THE AR-GROUND         FREQUENCY IN USE. IF UNABLE TO ESTABLISH CONTACT ON         ANY OF THE FOLLOWING EMERGENCY FREQUENCY ON THE AR-GROUND         PREQUENCY IN USE. IF UNABLE TO ESTABLISH CONTACT ON         UHFROULE IF FOLLOWING EMERGENCY FREQUENCIES:         UHFROULE WERGENCY FREQUENCIES:         UHFROULE WERGENCY FREQUENCIES:         243.0         243.0         243.0         ANY DAY, MAYDAY, MAYDAY         NAYDAY, MAYDAY, MAYDAY         NOAA         NOA         NATUDE         FLIGHT LEVEL OR ALTIT	NEXT DIST TIME ETA REMARKS PT DIST TIME ETA REMARKS TWO Khouls	10k 10k 10x5	LEN BRUK	
POSITION REPORT 15, 1. POSITION 11,00 2. TIME 4/ 3. ALTITUDE/0335 4. NEXT POSITION 6. NEXT POSITION	WS ALT TAS N	17 2,000 240	30 ISOww 262	
PAGE OF	DR +R=> -R=> -R=> -R= -R= -R= -R= -R= -R= -R= -R= -R= -R=	188 222 242 28		
	KERR MH VAR TH +			
11 0 mm 1 0 mm 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	KERR INS 2 POSITION KE	+ 103,53,55 + 1 + + + + + + + + + + + + + + + + +	102 11/02 12 102 20 20 20 11/1 295 34 21/14 20 21/14 20 21/	
CLANING OF	POSITION INS 1 POSITION	19:53 PES V 29:00 29:53 PES V 29:00 29:52 PES V 29:00 29:52 PES V 29:00 29:53 PES V 29:50 29:53 PES V 29:50 29:53 PES V 29:50 29:53 PES V 29:50 29:50 PES V 2	New Lillaury	
FREG ALT HDG E/5 EWA 10411	FIX TYPE V /S	2112 6 1012 2113 6 1013 2213 6 1013	2344 C 1032 Dolb C 1032	