U.S. DEPT. COMM./NORA/DAD - DATA SECTION WORK FORM NO.1 DADWE1 FILE FLT ID: 96 1707 H FM: BKF **TO:** RKF 4 FLT NO: 96-035 BLK IN: 0114 ATA: 0107 ETD: 2000 BLK OUT: 2127 ATD: 2137 ETE: 0200 BLK TIME: 3.8 FLT TIME: SPONSOR ORG: NOA PROGRAM: STERAO PURPOSE: PLATS ORO PERSONNEL AC ENNEDU PV SYS ENG ROLES CP GART DATA SYS 1CMIC(AN) NAV KO7 K RADAR FE TORREY BT/ODW RADID CLD PHYS FD WHI TH SV DOPPLER PARTICIPATING SCIENTIST/VISITORS/0A0 LAST, FIRST NAME ACTIVITY ON AVC 31-AFFILIATION #0 HUBLER, 6/JOBSON AC SHERDAN P CMDC WERT, B NCAR (GO(NAN) VI(THE) OCCOUNA! RTEI PROPOSED-ACTUAL MISSION-REMARKS (RECCO, FIXES, STORM, PENET, NHOP #) NSSC 30.04~ 1016.5 06 159

STERAO 96

FLIGHT #9 H960707

TYPE OF DATA	SENSOR OR OPTION
INE	1
Accelerometer	1
Temperature probe	1
Altitude change option	PA
(for vertical winds)	
Static pressure	Rosemount fuselage
Dynamic pressure	Rosemount fuselage
Time source	Micro 99
Constants file	CO2963, CON

Notes:

There were four time/data gaps: 2334:19 2334:30 0000:07 0000:10

The aircraft INE positions were renavigated with respect to GPS.

SPECIAL NOTE!!! Locations 80, 81 and 82 of record five on the standard tape contain vertical ground, vertical air and vertical speeds, respectively, computed using Dave Jorgensen's vertical wind algorithm. It is recommended that these values be used for vertical wind analysis.

Flight Meteorologist: Sean White: (813) 828-3310 ext. 3072

TITLE (MAX 21 CHARACTERS) -- EX HURRICANE PAINE STERAO FLIGHT 9 YYMMDDL FLT I.D. 960707H HHMMSS START TIME -99999 DEFAULT TO START OF DATA FOR PRINTOUT ONLY 213501 HHMMSS END TIME 999999 DEFAULT TO END OF DATA FOR PRINTOUT ONLY 011000 HHMMSS TAKE OFF TIME 213700 * NUMBER OF TAPES (12) ... FOR STANDARD TAPE OUTPUT ONLY 9 * -----LOGICAL UNIT OF INPUT DATA (I1) 5, 8 OR 9 FOR TAPE DRIVE 9 * -----LOGICAL UNIT OF OUTPUT TAPE DRIVE (11) [FOR STANDARD TAPE ONLY] 9 * -----LOGICAL UNIT OF PRINTER (11) 6 * -----DATE OF PROGRAM (MMDDY) 06094 * -----STATIC PRESSURE PROBE (11) * 1 = PSW (WINGTIP) * 2 = PSF (CO-PILOT/FUSELAGE) * 3 = FUTURE USE 2 * -----DYNAMIC PRESSURE PROBE (I1) * 0 = PQW(WINGTIP)* 1 = PQF1 (FUSELAGE 1281) * 2 = PQF2 (FUSELAGE 1221) * 3 =FUTURE US 1 * -----INE SELECTION (I1) * 1 = INE 1* 2 = INE 21 * -----ACCELEROMETER (I1) - USUALLY THE SAME AS YOUR INE SELECTION 1 * ----- TOTAL TEMPERATURE PROBE (I1) [1 OR 2] 1 * ----- DEWPONT TEMPERATURE PROBE (I1) [1 OR 2] 1 * -----ALTIMETER OPTION (I1) - FOR VERTICAL WIND COMPUTATION * 0 = PRESSURE ALTITUDE (OVER LAND) * 1 = RADAR ALTITUDE APN-159 (OVER WATER) * 2 = RADAR ALTITUDE APN-232 (OVER WATER) 0 * -----PRINTOUT RATE SECONDS (12) 30 * -----WINDSPEED/DIRECTION RUNNING AVERAGE TIME, SECONDS (12) 10 ! FOR STANDARD TAPE OUTPUT ONLY * -----TIME OPTION (I1) * 1 = MICRO 29 * 2 = TIME BASED GENERATOR #1 * 3 = TIME BASED GENEATOR #21 * -----NAME OF CONSTANTS FILE EX CO3863.CON CO2963.CON

960707H

START: 213501 END: 011000

BAD BL	OCK	
2334:	/	
13		
0000:0	17	
: /	0	
22000	+0.1	+0.1
20000		
230000	+0.4	40.4
00 000 C	+1,1	+0.6
011000	+1.3	+0,5

HC profile after the storm

North-South leg across the center of the last radar echo, the length of the HC-leg is approximately 100 km (not quite 1 deg latitude)

Hydrocarbon profile at 25 kft (or max altitude), 21 kft, 17 kft, 13 kft MSL, and 1500 ft AGL Start HC-leg at :05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**) 19:20-20:35

(0039-0055)

(Start NOy calibration, and stay at altitude for calibration 20:35-20:50, Observer calls)

Head direction of Buckley (39 42N, 104 45W) **Pt. A** ~ 20 min

Return to Buckley at ~21:00

Climb to 12 kft MSL for calibration

Pt. A (39 42N, 104 45W)
Pt. B (41 00N, 104 25W)
Pt. C (40 10N, 105 00W)
Pt. D (40 10N, 103 30W)
Pt. E (40 30N, 104 10W)
Pt. F (40 10N, 104 25W)
Pt. G (41 00N, 104 25W)
other points will be determined during the flight......

Concentrate on Western edge of squall line.

L-pattern on the southern (south-eastern) and the western side of the squall line.

I) Radar leg :	parallel to the line of storm cells at 2000 ft AGL from Lsw to Lse.
II) Radar leg :	return from Bse to Bsw at 500 ft AGL.
	Max length of these legs 15 min (~90 km).
III) Radar leg :	perpendicular to the line of storms at the western edge of the
	squall line, Bsw to Bnw at 500 ft AGL. Length of this leg is
	determined by radar requirement.
IV) Chemistry :	Return to Bse; either directly under the storm in a direct line from
	Bnw to Bse or parallel to the radar legs, but in closer proximity to
	the active storm cells at 500 ft AGL.

Repeat this pattern II)-IV), if radar observations call for it. Adjust altitude if radio communication with CHILL require it.

V) Racetrack profile ahead of the squall line up to max altitude.

VI) If there is an anvil within the altitude range of the P3, descend to that altitude and attempt to approach the anvil by flying short legs (< 5 min) parallel to the line in progressively closer proximity to the storm (pilots disgression).

VII) Fly to the back side of the squall line around the storm at max altitude. Attempt again to approach the anvil region.

40 45' 10402' Up + Dowy

VIII) Racetrack profile behind the squall line.

IX) Radar and chemistry leg behind the squall line from Bne to Bnw.

If the radar indicates an anvil that is within the altitude range of the P3, attempt to transect part of the anvil if it is feasible and safe. Start these transect away from the cloud and attempt to move closer on subsequent transects.

Hydrocarbon Profile between Pt. F and Pt. G (100, 10425W) (0007) (1000) (100(1-003) 500 Start HC-leg at : 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (Observer calls)

Flightplan Thunderstorm Study (with western variation) Colorado

boundary-layer to free troposphere exchange

Doors closed: 13:50 Takeoff: 14:00 2137 Point A, Buckley National Guard Field 39 42 N, 104 45W

Calibration at constant altitude, Observer calls (2152 - 2208)Head direction of Pt. B (41 00N, 104 25W) at 15 kft MSL

Pt. A to Pt. B 150 km, ~ 19 min, (Climb < 10 min)

Stay at constant altitude for calibration, observer calls 14:00-14:25

Before the Storm

The second second

2216

After Calibration descend to 1500 ft AGL along the way to Pt. C

Horizontal Survey within the PBL

Pt. B to Pt. C (40 10N, 105 00W), to Pt. D (40 10N, 103 30W), to Pt. E (40 30N, 104 10W) 14:25-15:10 230 14:23-13:10235023042Racetrack Profile up to 21 kft near Pt. E304230423002

==> Take first set of HC can samples at 1500 ft AGL, 13 kft, 17 kft, 21 kft MSL head east for 1 min 50 sec and climb at 1500 ft/min, reverse direction, head west for 1 min 50 sec, and continue climb etc up to 21 kft MSL) 15:10-15:20

Head direction of Pt. F (40 10N, 104 25W) Pt. E to Pt. F 60 km, 9 min 15:20-15:30

Super Cell

IF during any part of the flight Operation Center identifies an isolated storm, fly boxes around the storm at max altitude, 21 kft MSL, 17 kft MSL, 13 kft MSL, and 1500 ft AGL.

The sides of the boxes have to be long enough for the radar characterization of the wind field and the distance from the storm is determined by the requirements of the doppler radar. The exact location of the boxes at a given altitude will depend on the movement of the storm cell.

Should the time that is required to fly this pattern be too long for the anticipated flight duration, limit the number of constant altitude boxes.

This pattern should satisfy both the radar and chemistry objectives of STERAO.

15:35-16:35

If at any point during this leg the **Observation Center** at the CHILL Radar site should indentify a target storm, switch to the **Active Storm Phase**.

During the Active Storm Phase

Characterize Airflow with Radar and Characterize In-Flow Region of Cloud

Cloud identification and flight coordinates will be given by CHILL Radar.

Radar Legs:

Straight lines parallel to and S to SW of the storm approximately 12 km away from the perimeter of the storm, orientation parallel to storm track at 7kft MSL (within the PBL, this should also be the inflow region of the storm)

until dissipation of storm.

Alternatives:I) Straight leg parallel to the storm track.===>II) Fly L-pattern (south and west side of the storm).===>II) Repeat radar flight pattern at different altitude.
(7kft, 16 kft, and > 22 kft MSL).

16:35-18:35

After Dissipation of the Storm:

Characterization of PBL after Storm Dissipation: Cross below location of the latest radar echo for 15 min (~100 km) 18:35-18:50

Characterization of Vertical Profile after Storm Dissipation

Race track Profile at location of the latest radar echo of the storm, descend to 500 ft AGL and then climb to max altitude at 1500 ft/min

==> Take second set of HC can samples at 1500 ft AGL, 13 kft, 17 kft, 21 kft MSL 18:50-19:20

Alternatives:

I) 16:35-17:50: If there is no appropriate storm identified in the study area, start HC profile between Pt. F (40 10N, 104 25W), and Pt. AH (40 10N, 103 25 W) at 1500 ft AGL, 13 kft MSL, 17 kft MSL, 21 kft MSL, 25 kft MSL.

II) 17:50-19:05: start HC profile between Pt. AH (40 10N, 103 25W) and AI (41 00N, 103 25W) at 25 kft MSL, 21 kft MSL, 17 kft MSL, 13 kft MSL, 1500 ft AGL

Climb to 12 kft MSL for calibration, 30 min

Return to Buckley

The detailed characterization of the 1 deg lat by 1 deg long box will hopefully help to pick the most appropriate orientation for the HC profiles for subsequent flights. It also allows to fall back into the thunderstorm mode at any time if appropriate storms should develop later on.

Alternative Orographic profile and Profile near Kremmling:

I) HC-Profile to the West of Ft. Collins.

Cross to Pt. BH (40 10N, 105 10 W) and adjust time for HC-Profile by flying N at 500 ft AGL and return to BH at start of HC profile If there is no appropriate storm identified in the study area, start HC profile between Pt. BH (40 10N, 105 10W), and Pt. BI (41 00N, 105 10 W) at 8 kft MSL, 13 kft MSL, 17 kft MSL, 21 kft MSL, 25 kft MSL. Start HC-leg at : 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**) 16:35-18:05:

II) HC-Profile near Kremmling
Head direction of Pt. BJ (41 00N, 106 30W) at 25 kft MSL
(Pt. BI to Pt. BJ 110 km, ~ 15 min) 18:05-18:20
HC Profile between Pt. BJ (41 00N, 106 30 W) and Pt. BK (40 00 N, 106 30 W)
at 21 kft MSL, 17 kft MSL, 15 kft MSL, 11 kft MSL (> 500 ft AGL)
Start HC-leg at : 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (Observer calls)
18:20-19:20

Climb to 15 kft MSL and return to Buckley, Calibration along the way. (Pt. BJ to Buckley 210 km, ~ 30 min) 19:50 7

Time	TA	TD	wD	ws	12	C	In	ce	A	2.5			~		1
<u>ai37</u>			090	4	T	10									
2124	2,4	-9,1	287	73.9	(20	lel	12-12			ļ					
											1				-
													1		
										ļ					
										<u> </u>					
							-					i			<u>.</u>
					-		ļ		-						
												1	<u> </u>		-
					1					+	<u>.</u>				
			-									 			
					1							i	<u> </u>		
													1		
											ļ				
									<u>i</u>						
-															
				ing the second	ļ							1	<u> </u>		
									1			1			
		14						v				1		<u> </u>	
											-				÷
										ļ					
															-
															+
						· · ·									1
				•											
															<u> </u>
				•											
											<u></u>				
_							•0					5			
										-					
				•											

: 7 July 96	
: Chief, AOC Flig	ght Operations ON 2139 BLOCKTIN
: Pilot/Flight Di	irector, Aircraft $\frac{N42RT}{2}$
CT: Hazardous Duty	UFF <u>U</u> I <u>U</u> <u>I</u> <u>U</u> <u>U</u> <u>I</u> <u>U</u> <u>U</u> <u>I</u> <u>U</u> <u></u>
PURPOSE OF FLIGHT:	STERAD
Hazardous Duty Pay	is required for flight made on $\frac{2}{2} \int u(y) dy$
Request based on _	POISONOUS GASES
_	ONBOARD
Personnel on board TORREY R ROCES J	authorized Hazard Pay:
Personnel on board TORREY, R ROCES, J MCMILLAN, S	authorized Hazard Pay:
Personnel on board TORREY, R ROCES, J MCMILLAN, S	authorized Hazard Pay:
Personnel on board TORREY, R ROCES, J MCMILLAN, S	authorized Hazard Pay:
Personnel on board TORREY, R ROCES, J MCMILLAN, S	authorized Hazard Pay:
Personnel on board TORREY R ROCES J MCMICLAN, S PILOT/FLIGHT DIREC	authorized Hazard Pay:

i

.

MESSAGE	LISH COMMS, ATTEMPT CONTACT ON QUENCIES:	HF/CW MF/CW 8364 KHZ 500 KHZ	NOAA	N/S E/W AT		SOULS ON BOARD	E REMAINING	REMARKS	Enlo/chours	Tax,	TOPP	LEWEL OF			REGIN Cal	UN Bulf	c hoeks							
ERGENCY	ALE TO ESTABI ERGENCY FRE	MF/VOICE 2182 KHZ	DAY	1	E/MAG INDICATED	TUDE T WITH	ENDURANCI	ETA	-															
EME	USE. IF UNAL	VHF/VOICE 121.5	AVDAY, MAY		TRU KTS TRUE	VEL OR ALT P-3 AIRCRAI F EMERGEN	CE DESIRED	TIME									-							
	REQUENCY IN	JHF/VOICE 43.0	AAYDAY, M/	POSITION	HEADING	FLIGHT LEV WE ARE A I NATURE OI	ASSISTANC PILOT INTE WE HAVE	DIST																
	4	54		•				NEXT PT																
REPORT					SITION		SITION	TAS			-	250	220	283	254		-							
OSITION		OSITION	IIME		VEXT PO:	ETA	VEXT PO	ALT	а 			(5)00	c'eac	2),00	Cm (2)									
<u></u>			~		4		.	MS	£.			52	2	5	23									
T						er.	158	ß				1967	1050	292	R									
OF _	000			S	2		1	GS				58	252	206	27		-							
ЭЕ	4	X		\bigcirc			1 Jour	TRK	1			09.5	306	001	R									
PAG		400	J	8		933		BR [†]	82			4	ノ	8.4	30		2				ģ. 123			
IJ				8	**	138		E				310	30	32	12									
SION LO		X				X	den f	VAR +E==>				910	₩Ţ	505	5									
MISS	8	×		308				R MH	-		1	0.01	100 -	340	K 30				1		1	i.	-	
							1010	I K ERI			1 1 1 	イナキ	5 1 1 1		547		ţ.			i i		4 4 1 1		
						Long L		POSITION	• /		1 1 1	12.52 1941 1941	295	いの	VESS		V8/11 VSTA		1					
						Å	34	INS 21	7			8è	101	ēé Ţ	- 20-	•	39	-			1 1 1 1	1		T T
	œ		¥	400		30/		K ERR				Q4	17 ++	5- 	OFF		+++					1	.1 1 1 1	
	OTHE		401	1741		,	90	OSITION				53 53	2121	N 9 N	2.0h		20.95				1 			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ANCES		N N						INS 1 P	2 -			s hu	101-	₹Ś.	1010		1044							
CLEAR	g			_	$\left \right $			TION	SS		-	230	して	23	245	22	220		1					
	모							POSI	Super Super	F	1	Sent I	1024	5010	107	ナシャ	50 L2) - - - - -				 		
	ALT							FIX TYPE	5		i	0	٩	2	1		~ ~ ~							
	FREQ							TIME	2123	noc	5518	M	250	Shez	ones	Lut.	/ 1							

۹. 1