U.S. DEPT. COMM./NORA/DAO - DATA SECTION WORK FORM NO.1 DADWET FI									
760 70917	FM: Bk	F	TO: BEF						
FLT NO: 96 -	BLK IN: D3		ATA: 031.0						
ETD: 2000	BLK DUT: 2		ATD: 2130						
ETE: 0200	BLK TIME: 5		FLT TIME:						
SPONSOR ORG: NOA.A	PROGRAM: ST	FR AO	PURPOSE: A. diemistry						
	OAO PERSO	The second lives and the second lives are a second lives and the second lives are a second lives and the second lives are a sec	H. v. Chemistry						
ACKENNEDY, P	V :	SYS ENG	ROCESJU						
CP TAGGART B		DATA SYS	MCMPH LA C						
NAV STRONG, TU	/	RADAR	MCMTCLAN, SL						
FE WADES V		DT/ODW							
RADIO		CLD PHYS							
FD WHITE, S-		DOPPLER							
PARTICIPATING SCIENTIST/VISITORS/0A0									
LAST, FIRST NAME									
MCFADENJV	ACTIVITY ON A		AFFILIATION						
HUBLER G	Air Che	us tus	NOAT						
KUSTER RYERSON									
SHERIDAN, P			AC						
WERT, B			CMDC						
ROBERTS/JOBSON			NCAR						
HOLLOWAYX			AC						
GATEJEA RARTES ALDAS									
PROPOSED/ACTUAL MISSION/REMARKS (RECCO, FIXES, STORM, PENET, NHOP #)									
30,14 ~ 1029.5	310/08/026		, FEREI, NHOP #)						
NAU updations	FNE#2								
1011166									
Radavis Trop & 2002									
. US	0/14								
	E								
			1						

NO DATA DISPOSITION/DATE/OUALITY 1/SEC FLT LVL TAPES FAST FLT LVL TAPES RADAR TAPES DOPPLER TAPES DOW CASSETTES HARD COPIES AXBT AXCP	OROWF2 WX STN
TIME OFF: TIME ON: A/C T/O WX STN A/C LAND PRESSURE NO DATA DISPOSITION/DATE/OUALITY A/SEC FLT LVL TAPES FAST FLT LVL TAPES COPPLER TAPES DOM CASSETTES HARD COPIES AXADT AXADT PHOTOGRAPHY FMD LS RS VERT	
PRESSURE NO DATA DISPOSITION/DATE/OUALITY NSEC FLT LVL TAPES FAST FLT LVL TAPES RADAR TAPES DOPPLER TAPES DOWN CASSETTES HARD COPIES RXDT AXCP ODW 7 PHOTOGRAPHY FWD LS RS VERT	WX STN
PRESSURE NO DATA DISPOSITION/DATE/OUALITY 1/SEC FLT LVL TAPES FAST FLT LVL TAPES RADAR TAPES DOPPLER TAPES ODM CASSETTES HARD COPIES AXBT AXCP ODM FMD FMD LS RS VERT	
1/SEC FLT LVL TAPES FAST FLT LVL TAPES RADAR TAPES DOPPLER TAPES DDW CASSETTES HARD COPIES AXBT AXCP ODW FHOTOGRAPHY FWD LS RS VERT	
TYSEC FLT LVL TAPES FAST FLT LVL TAPES RADAR TAPES DOPPLER TAPES DDW CASSETTES HARD COPIES AXBT AXCP ODW FWD LS RS VERT	
FAST FLT LVL TAPES RADAR TAPES DOPPLER TAPES DDW CASSETTES HARD COPIES AXBT AXCP ODW PHOTOGRAPHY FWD LS RS VERT	
DOPPLER TAPES DDW CASSETTES HARD COPIES AXBT AXCP DDW PHOTOGRAPHY FWD LS RS VERT	
DDW CASSETTES HARD COPIES AXBT AXCP ODW 7 PHOTOGRAPHY FWD LS RS VERT	
DDW CASSETTES HARD COPIES AXDT AXCP ODW 7 PHOTOGRAPHY FWD LS RS VERT	
AXBT AXCP ODW ; PHOTOGRAPHY FWD LS RS VERT	
AXBT AXCP ODW ; PHOTOGRAPHY FWD LS RS VERT	
AXDT AXCP ODW PHOTOGRAPHY FWD LS RS VERT	
AXDT AXCP ODW PHOTOGRAPHY FWD LS RS VERT	,
AXDT AXCP ODW PHOTOGRAPHY FWD LS RS VERT	
PHOTOGRAPHY FWD LS RS VERT	
PHOTOGRAPHY . FWD LS RS VERT	.·
PHOTOGRAPHY . FWD LS RS VERT	
FWD LS RS VERT	
FWD LS RS VERT	
FWD LS RS VERT	
OFF	
RATE	
REMARKS	
	es ;
	•

ď,

FLIGHT #10 H960709

TYPE OF DATA	SENSOR OR OPTION
INE	1
Accelerometer	ī
Temperature probe	1
Altitude change option	PA
(for vertical winds)	
Static pressure	Rosemount fuselage
Dynamic pressure	Rosemount fuselage
Time source	Micro 99
Constants file	CO2963.CON

Notes:

There were seventeen time/data gaps: 2249:27 2249:28 2249:29 2249:30 0057:36 0057:37 0057:38 0057:39 0057:40 0141:11 0141:20 0207:55 0207:56 0207:57 0207:58 0207:59 0208:00

DW1 (Dewpoint #1) replaced with DW2 (Dewpoint #2).

APN-159 radar altimeter inop at time 2137Z. APN-159 replaced with APN-232 from 2128:11 thru 2305:00.

SPECIAL NOTE!!! Locations 80, 81 and 82 of record five on the standard tape contain vertical ground, vertical air and vertical speeds, respectively, computed using Dave Jorgensen's vertical wind algorithm.

It is recommended that these values be used for vertical wind analysis.

Flight Meteorologist: Sean White: (813) 828-3310 ext. 3072

```
TITLE (MAX 21 CHARACTERS) -- EX HURRICANE PAINE
STERAO FLIGHT 10
YYMMDDL FLT I.D.
960709H
HHMMSS START TIME -99999 DEFAULT TO START OF DATA FOR PRINTOUT ONLY
212811
HHMMSS END TIME 999999 DEFAULT TO END OF DATA FOR PRINTOUT ONLY
031100
HHMMSS TAKE OFF TIME
213000
* NUMBER OF TAPES (I2) ...FOR STANDARD TAPE OUTPUT ONLY
* -----LOGICAL UNIT OF INPUT DATA (I1) 5, 8 OR 9 FOR TAPE DRIVE
* -----LOGICAL UNIT OF OUTPUT TAPE DRIVE (I1) [FOR STANDARD TAPE ONLY]
* -----LOGICAL UNIT OF PRINTER (I1)
* -----DATE OF PROGRAM (MMDDY)
06094
* ----STATIC PRESSURE PROBE (I1)
* 1 = PSW (WINGTIP)
* 2 = PSF (CO-PILOT/FUSELAGE)
* 3 = FUTURE USE
* -----DYNAMIC PRESSURE PROBE (I1)
* 0 = PQW(WINGTIP)
* 1 = PQF1 (FUSELAGE 1281)
* 2 = PQF2 (FUSELAGE 1221)
* 3 =FUTURE US
1
* ----- INE SELECTION (I1)
* 1 = INE 1
* 2 = INE 2
* -----ACCELEROMETER (I1) - USUALLY THE SAME AS YOUR INE SELECTION
1
* ----- TOTAL TEMPERATURE PROBE (I1) [1 OR 2]
1
* ----- DEWPONT TEMPERATURE PROBE (I1) [1 OR 2]
2
* -----ALTIMETER OPTION (I1) - FOR VERTICAL WIND COMPUTATION
* 0 = PRESSURE ALTITUDE (OVER LAND)
* 1 = RADAR ALTITUDE APN-159 (OVER WATER)
* 2 = RADAR ALTITUDE APN-232 (OVER WATER)
0
* -----PRINTOUT RATE SECONDS (I2)
10
* -----WINDSPEED/DIRECTION RUNNING AVERAGE TIME, SECONDS (12)
10
                               ! FOR STANDARD TAPE OUTPUT ONLY
* ----TIME OPTION (I1)
* 1 = MICRO 29
* 2 = TIME BASED GENERATOR #1
* 3 = TIME BASED GENEATOR #2
1
* -----NAME OF CONSTANTS FILE EX CO3863.CON
CO2963.CON
*************************
```

Concentrate on Western edge of squall line.

L-pattern on the southern (south-eastern) and the western side of the squall line.

I) Radar leg:

parallel to the line of storm cells at 2000 ft AGL from Lsw to Lse.

II) Radar leg:

return from Bse to Bsw at 500 ft AGL.

Max length of these legs 15 min (~90 km).

III) Radar leg:

perpendicular to the line of storms at the western edge of the

squall line, Bsw to Bnw at 500 ft AGL. Length of this leg is

determined by radar requirement.

IV) Chemistry:

Return to Bse; either directly under the storm in a direct line from

Bnw to Bse or parallel to the radar legs, but in closer proximity to

the active storm cells at 500 ft AGL.

Repeat this pattern II)-IV), if radar observations call for it. Adjust altitude if radio communication with CHILL require it.

- V) Racetrack profile ahead of the squall line up to max altitude.
- VI) If there is an anvil within the altitude range of the P3, descend to that altitude and attempt to approach the anvil by flying short legs (< 5 min) parallel to the line in progressively closer proximity to the storm (pilots disgression).
- VII) Fly to the back side of the squall line around the storm at max altitude. Attempt again to approach the anvil region.
- VIII) Racetrack profile behind the squall line.

TVI	Dadamand	al aminture	laa bakind	the servall	Line frame	Dwg to Dwy
	Kadar and	chemistry	ieg benina	the squan	nne trom	Bne to Bnw.
		T	8			

If the radar indicates an anvil that is within the altitude range of the P3, attempt to trans	ısect
part of the anvil if it is feasible and safe. Start these transect away from the cloud and	
attempt to move closer on subsequent transects.	

Hydrocarbon Profile between Pt. F and Pt. G

At 15:35 head direction of Pt. G (41 00N, 104 25W)

Hydrocarbon profile between Pt. F and Pt. G at 21 kft, 17 kft, 13 kft MSL, and 1500 ft AGL Start HC-leg at: 05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**)

15:35-16:35

If at any point during this leg the **Observation Center** at the CHILL Radar site should indentify a target storm, switch to the **Active Storm Phase.**

During the Active Storm Phase

Characterize Airflow with Radar and Characterize In-Flow Region of Cloud

Cloud identification and flight coordinates will be given by CHILL Radar.

Radar Legs:

Straight lines parallel to and S to SW of the storm approximately 12 km away from the perimeter of the storm, orientation parallel to storm track at 7kft MSL (within the PBL, this should also be the inflow region of the storm)

until dissipation of storm.

Alternatives:

I) Straight leg parallel to the storm track.

===>

II) Fly L-pattern (south and west side of the storm).

===>

II) Repeat radar flight pattern at different altitude.

(7kft, 16 kft, and > 22 kft MSL).

16:35-18:35

After Dissipation of the Storm:

Characterization of PBL after Storm Dissipation:

Cross below location of the latest radar echo for 15 min (~100 km)

18:35-18:50

Characterization of Vertical Profile after Storm Dissipation

Race track Profile at location of the latest radar echo of the storm, descend to 500 ft AGL and then climb to max altitude at 1500 ft/min

==> Take second set of HC can samples at 1500 ft AGL, 13 kft, 17 kft, 21 kft MSL 18:50-19:20

960709H

BAD BLOCKS

22 49: 27

:78

: 29

:30

0057:36

0141:11

: 20

0207:55-59

0908:00

START: 21280+

END: 031100

APN 159 INOP 21377

RAI W RAZ

219811 - 5301-00

DUT of DWF

HC profile after the storm

North-South leg across the center of the last radar echo, the length of the HC-leg is approximately 100 km (not quite 1 deg latitude)

Hydrocarbon profile at 25 kft (or max altitude), 21 kft, 17 kft, 13 kft MSL, and 1500 ft AGL Start HC-leg at :05, :20, :35, :50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**) 19:20-20:35

Climb to 12 kft MSL for calibration (Start NOy calibration, and stay at altitude for calibration 20:35-20:50, Observer calls)

Head direction of Buckley (39 42N, 104 45W) Pt. A ~ 20 min

Return to Buckley at ~21:00

Pt. A (39 42N, 104 45W)

Pt. B (41 00N, 104 25W)

Pt. C (40 10N, 105 00W)

Pt. D (40 10N, 103 30W)

Pt. E (40 30N, 104 10W)

Pt. F (40 10N, 104 25W)

Pt. G (41 00N, 104 25W)

other points will be determined during the flight......

Alternatives:

I) 16:35-17:50: If there is no appropriate storm identified in the study area, start HC profile between Pt. F (40 10N, 104 25W), and Pt. AH (40 10N, 103 25 W) at 1500 ft AGL, 13 kft MSL, 17 kft MSL, 21 kft MSL, 25 kft MSL.

II) 17:50-19:05: start HC profile between Pt. AH (40 10N, 103 25W) and AI (41 00N, 103 25W) at 25 kft MSL, 21 kft MSL, 17 kft MSL, 13 kft MSL, 1500 ft AGL

Climb to 12 kft MSL for calibration, 30 min

Return to Buckley

The detailed characterization of the 1 deg lat by 1 deg long box will hopefully help to pick the most appropriate orientation for the HC profiles for subsequent flights. It also allows to fall back into the thunderstorm mode at any time if appropriate storms should develop later on.

Alternative Orographic profile and Profile near Kremmling:

I) HC-Profile to the West of Ft. Collins.

Cross to Pt. BH (40 10N, 105 10 W) and adjust time for HC-Profile by flying N at 500 ft AGL and return to BH at start of HC profile

If there is no appropriate storm identified in the study area, start HC profile between Pt. BH (40 10N, 105 10W), and Pt. BI (41 00N, 105 10 W)

at 8 kft MSL, 13 kft MSL, 17 kft MSL, 21 kft MSL, 25 kft MSL.

Start HC-leg at: 05,:20,:35,:50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**) 16:35-18:05:

II) HC-Profile near Kremmling

Head direction of Pt. BJ (41 00N, 106 30W) at 25 kft MSL

(Pt. BI to Pt. BJ 110 km, ~ 15 min) 18:05-18:20

HC Profile between Pt. BJ (41 00N, 106 30 W) and Pt. BK (40 00 N, 106 30 W)

at 21 kft MSL, 17 kft MSL, 15 kft MSL, 11 kft MSL (> 500 ft AGL)

Start HC-leg at: 05,:20,:35,:50 so that the HC sample will be centered along this leg. Change altitude approximately 3 min after HC sample ends (**Observer calls**) 18:20-19:20

Climb to 15 kft MSL and return to Buckley, Calibration along the way. (Pt. BJ to Buckley 210 km, ~ 30 min) 19:50

	Flightplan Thunderstorm Study (with western variation) Colorado boundary-layer to free troposphere exchange							
	Doors closed: 13:50 Takeoff: 14:00 Point A, Buckley National Guard Field 39 42 N, 104 45W							
	Calibration at constant altitude, Observer calls 12/ (21 -2154) Head direction of Pt. B (41 00N, 104 25W) at 18 kft MSL							
	Pt. A to Pt. B 150 km, ~ 19 min, (Climb < 10 min)							
	Stay at constant altitude for calibration, observer calls 14:00-14:25							
	Before the Storm After Calibration descend to 1500 ft AGL along the way to Pt. C							
22002_	After Calibration descend to 1500 ft AGL along the way to Pt. C Horizontal Survey within the PBL Pt. B to Pt. C (40 10N, 105 00W), to Pt. D (40 10N, 103 30W), to Pt. E (40 30N, 104 10W) 14:25-15:10							
2 7)	Racetrack Profile up to 21 kft near Pt. E ==> Take first set of HC can samples at 1500 ft AGL, 13 kft, 17 kft, 21 kft MSL head east for 1 min 50 sec and climb at 1500 ft/min, reverse direction, head west for 1 min 50 sec, and continue climb etc up to 21 kft MSL) 15:10-15:20							
0055	15:10-15:20 Head direction of Pt. F (40 10N, 104 25W) Pt. E to Pt. F 60 km, 9 min 15:20-15:30 15:10-15:20 15:20-15:30							
20 r								
	Super Cell							
	IF during any part of the flight Operation Center identifies an isolated storm, fly boxes							
10 to to	around the storm at max altitude, 21 kft MSL, 17 kft MSL, 13 kft MSL, and 1500 ft AGL.							
	The sides of the boxes have to be long enough for the radar characterization of the wind field and the							
	distance from the storm is determined by the requirements of the doppler radar. The exact location of							
40	the boxes at a given altitude will depend on the movement of the storm cell. Should the time that is required to fly this pattern be too long for the anticipated flight							
_	duration, limit the number of constant altitude boxes.							
	This pattern should satisfy both the radar and chemistry objectives of STERAO.							
2	Zamo Paristra 2770 mm and 277 mm							

Squall Line

13,17,21

	3							1								
Time	TA	TO	WD	1.15	10		ma;	1/1.			i	Ţ	1			Ī
T. we	12	10	UVD	Iw	1	12	nec	400	5		İ		-			
					au	1 9	ma;	e in	s d	0 6 (7	1	1	-		
					V	racla	av	0/6	Va	clar	- 0	valle		1-		
						-	-		-							
								1	 	+			-			
												i -				
						-		-	+							
						-			 			+	-	+		
														1	1	- /×
-					+	 		-	-					-		
							1	-	l			 	-	-		- 44
											1			1+	<u> </u>	
						-	-		-	ļ						
	*						1	 	-	-				++		
											İ	1	1	++	-	
						 	ļ	<u> </u>	<u> </u>		-					
						-	<u> </u>	 	1	+	-	!	 	-		-
			*										 	1		
						-	<u> </u>					į.				
							 		 	-		1	+	ļ		
												 	 	-		_
															10000	
									-		-	1				
														-		
		-	-		1			 							Ī	
												-	-			
													1			
															i	
												-	-		- !	
											 		 	-	- 1	
										-		-	ļ			
											COMMAND TO THE REAL PROPERTY OF THE PERTY OF	<u> </u>			\dashv	
												-				
												-	-		\dashv	
														5		
	-								100							
													V .		-	
															_	<u> </u>
					а	1,550										
								/								
														-		

DATE	:9July 96		v
TO	: Chief, AOC Flig	ght Operations	BLOCKTIME
FROM	: Pilot/Flight Di	irector, Aircraft N4DE OFF 2118	
SUBJE	CT: Hazardous Duty	OFF ATTO	
	PURPOSE OF FLIGHT:		···,
	Hazardous Duty Pay	is required for flight made on	9 July 96 (DATE)
3.	Request based on _	POISONOUS GASES	
		· 010 BOARD	
8	4		-
	Personnel on board WADE, S ROLES J MCMT/(AA)	authorized Hazard Pay:	
SM	MCHABEN, MCFADDEN,	JSW	
	PILOT/FLIGHT DIREC	TOR: LCDR SEAN R. WH	· FITE
	APPROVED:	DISAPPROVED:	
	CHIEF, AOC FLIGHT	OPERATIONS:	

26 /44s

TRANSMIT THE FOLLOWING MESSAGE TO ANY AGENCY ON THE AIR-GROUND FREQUENCY IN USE. IF UNABLE TO ESTABLISH COMMS, ATTEMPT CONTACT ON ANY OF THE FOLLOWING EMERGENCY FREQUENCIES: SOULS ON BOARD REMARKS UHF/VOICE VHF/VOICE MF/VOICE HF/CW MF/CW 243.0 121.5 2182 KHZ 8364 KHZ 500 KHZ N/S E/W AT **EMERGENCY MESSAGE** ENDURANCE REMAINING MAYDAY, MAYDAY
THIS IS NOAA _____ NOAA _____ HEADING TRUEMAG

- AT KTS TRUE/INDICATED

- FLIGHT LEVEL OR ALTITUDE

- WE ARE A P-3 ARCRAFT WITH

- NATURE OF EMERGENCY

- ASSISTANCE DESIRED

- PILOT INTENTIONS

- WE HAVE ENDURANCE ETA TIME DIST - POSITION NEXT PT POSITION REPORT TAS 4. NEXT POSITION 6. NEXT POSITION 3. ALTITUDE 1. POSITION ALT 5. ETA WS Š 1200 GS P TR 9 PAGE gates **₽** F **MISSION LOG** VAR Ħ Ξ K ERR INS 2 POSITION 270 K ERR OTHER INS 1 POSITION 24-42.8 CLEARANCES 39-42,3 POSITION HDG ALT FIX TYPE FREQ 1957 25% 030